



Halogen reflector

13528 15W GZ4 6V 1CT/24

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data

General Information			
Cap-Base	GZ4 [GZ4]		
Philips Code	13528		
ANSI Code	-		
LIF Code	-		
Operating Position	S105 [s105]		
Main Application	Projection		
Life to 50% Failures (Nom)	750 h		
J Code	-		
Light Technical			
Correlated Color Temperature (Nom)	2900 K		
Color Rendering Index (Nom)	100		
Operating and Electrical			
Power (Rated) (Nom)	15 W		
		$\overline{}$	

Voltage (Nom)	6 V	
Controls and Dimming		
Dimmable	Yes	
Mechanical and Housing		
Cap-Base Information	-	
Bulb Material	Quartz-UV Open	
Reflector Finish	Smooth	
Filament Shape	-	
Filament Dimensions WxH	-	
Luminaire Design Requirements		
Bulb Temperature (Max)	900 °C	
Pinch Temperature (Max)	350 °C	


Datasheet, 2017, November 2 data subject to change

Halogen reflector

Working Distance WD	92 mm	
Product Data		
Full product code	871869668993600	
Order product name	13528 15W GZ4 6V 1CT/24	
EAN/UPC - Product	8718696689936	
Order code	923883810105	

Numerator - Quantity Per Pack	1	
Numerator - Packs per outer box	24	
Material Nr. (12NC)	923883810105	
Net Weight (Piece)	12.000 g	

Dimensional drawing



13528 15W GZ4 6V

Product	D (max)	C (max)
13528 15W GZ4 6V 1CT/24	35 mm	42 mm

