

Outdoor light

DL Vario Quattro LED

EAN 4007841035440



Functional description

The LED ceiling light with precise detection. The four infrared sensors can be mechanically adjusted in each direction from 2 to 8 m to suit any need. 360° all-round detection is ideally suited for optimum adjustment to the local situation, e.g. carports and porches. The light diffuser also acts as the sensor lens - a patented world first. The ceiling light provides 1000 lm of illumination at an output of 10 W and can be mounted at heights of up to 6 m, including a convenient night light function (10%) at twilight.

Technical specifications

Dimensions (Ø x H)	310 x 69 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
max	6,00 m
Sensor Technology	passive infrared
Sensor	No
Luminous flux	1000 lm
Efficiency	100 lm/W
Colour temperature	3000 K
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	Yes
Reach, detail	Reichweite von 2 - 8 m in 4 Richtungen (je 90 °) einstellbar
Reach, radial	4 x 4 m (16 m ²)
Reach, tangential	16 x 16 m (256 m ²)
Photo-cell controller	Yes
Twilight setting	2 – 1000 lx
Time setting	5 s – 30 min
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Soft light start	Yes
Continuous light	selectable, 4h
Impact resistance	IK07
IP rating	IP54
Protection class	II

<https://www.steinell.de/>

Outdoor light

DL Vario Quattro LED

EAN 4007841035440

Ambient temperature	-20 – 35 °C
Housing material	Plastic
Cover material	Plastic, structured
Manufacturer's Warranty	3 years
With remote control	No