

Motion detector

IS 3360

EAN 4007841010478



Functional description

Large spaces, multi-storey car parks and production buildings with ceiling heights of up to 4 m rarely provide installation surfaces every metre. These environments call for motion detectors with a long reach. Like the IS 3360. It detects any tangential movement within an all-round radius of 20 metres. Even installed at heights of up to 4 metres. In short: one IS 3360 covers an area of more than 1000 m²! STEINEL Infrared technology that keeps its promises.

Technical specifications

| | |
|--|--------------------------|
| Type | Motion detectors |
| Dimensions (L x W x H) | 95 x 95 x 65 mm |
| Mains power supply | 220 – 240 V , 50 / 60 Hz |
| Sensor Technology | passive infrared |
| Type of installation | Surface wiring |
| Switching zones | 1416 Schaltzonen |
| Electronic scalability | No |
| Mechanical scalability | No |
| Mounting height | 2,50 – 4,00 m |
| Optimum mounting height | 2,8 m |
| Detection angle | 360 ° |
| Angle of aperture | 180 ° |
| Sneak-by guard | Yes |
| Capability of masking out individual segments | Yes |
| Reach, radial | Ø 10 m (79 m²) |
| Reach, tangential | Ø 40 m (1257 m²) |
| Reach, presence | Ø 3 m (7 m²) |
| Twilight setting TEACH | Yes |
| Twilight setting | 2 – 1000 lx |
| Time setting | 5 s – 15 min |
| Switching output 1, resistive | 2000 W |
| Switching output 1, number of LEDs / fluorescent lamps | 8 stk. |
| Constant-lighting control | No |
| Basic light level function | No |
| With remote control | No |
| Interconnection | Yes |
| IP rating | IP54 |
| Material | Plastic |
| Ambient temperature | -20 – 50 °C |
| Colour | white |
| Colour, RAL | 9003 |
| Manufacturer's Warranty | 5 years |

Motion detector

IS 3360

EAN 4007841010478

Version

COM1 - surface-mounted installation, square

Motion detector

IS 3360

EAN 4007841010478

Sensorenerfassungsbereich 1

