### Data sheet



#### Outdoor light

# L 825 LED iHF

EAN 4007841007164





#### **Functional description**

Some like it classic. This is why we have combined the pioneering technology and unique functionality of the iHF series with timeless design. The result – the L 825 LED iHF – setting off your front door with permanent aesthetic appeal. Needless to say, only when needed: the sensor detects persons approaching from any direction –and can distinguish them from small animals. And it remains completely invisible. With minimal energy consumption and the incredibly long life expectancy of the LEDs, so too are its running costs.

#### **Technical specifications**

Dimensions (L x W x H)	95 x 331 x 157 mm
Mains power supply	230 – 240 V , 50 / 60 Hz
Sensor Technology	iHF (intelligent high-frequency technology)
Transmitter power	< 1 mW
Output	12 W
Luminous flux	400 lm
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Active and Passive Thermo Control
With motion detector	Yes
Detection angle	160 °
Sneak-by guard	Yes
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	$r = 5 \text{ m} (35 \text{ m}^2)$
Reach, tangential	$r = 5 \text{ m} (35 \text{ m}^2)$
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Soft light start	Yes
Continuous light	selectable, 4h
IP rating	IP44
Protection class	II.
Ambient temperature	-20 – 50 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	3 years

https://www.steinel.de/

## Data sheet



Outdoor light

# L 825 LED iHF

EAN 4007841007164

**Version** aluminium-anthracite