#### **DATASHEET - AK-PKZ0**



#### Rotary handle, lockable

Part no. AK-PKZ0
Catalog No. 030851
Eaton Catalog No. XTPAXLRH
EL-Nummer 0004355090
(Norway)



### **Delivery program**

Product range	Accessories
Accessories	Rotary handle, lockable
	for locking motor-protective circuit-breakers PKZM0, PKZM4 and PKE as a main switch in compliance with EN 60204 Can be padlocked in the "0" position with a padlock Hasp thickness: 3 — 6.35 mm
For use with	PKZM0 PKZM4 PKZM0-T PKM0 PKE

Notes Cannot be used in combination with VHI20-PKZ0. Usable add-on front plates: ZFS...-T0 or ZFS...-P3

17 x 48 mm or 27 x 88 mm and ZFS60-NZM7

17 x 64 mm

For use on surface-mounted and installation housings.

### Design verification as per IEC/EN 61439

Design verincation as per illo/liv 01433			
Technical data for design verification			
Rated operational current for specified heat dissipation	In	Α	0
Heat dissipation per pole, current-dependent	$P_{\text{vid}}$	W	0
Equipment heat dissipation, current-dependent	P <sub>vid</sub>	W	0
Static heat dissipation, non-current-dependent	P <sub>vs</sub>	W	0
Heat dissipation capacity	P <sub>diss</sub>	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			Not applicable.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.


## **Technical data ETIM 7.0**


Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)				
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss10.0.1-27-37-04-14 [AKF012014])				
Lockable	Yes			
Colour	Black			
Suitable for emergency stop	No			
With extension shaft	No			
Suitable for power circuit breaker	No			
Suitable for switch disconnector	Yes			

# Approvals

Product Standards	UL 508; CSA-C22.2 No. 14; IEC60947-4-1; CE marking
UL File No.	E36332
UL Category Control No.	NLRV
CSA File No.	165628
CSA Class No.	3211-05
North America Certification	UL listed, CSA certified
Specially designed for North America	No

# **Dimensions**





## **Additional product information (links)**

Motor starters and "Special Purpose Ratings" for the North American market

Busbar Component Adapters for modern Industrial control panels

http://www.eaton.eu/ecm/groups/public/@pub/@europe/@electrical/documents/content/pct\_3258146.pdf http://www.moeller.net/binary/ver\_techpapers/ver960en.pdf