



High quality and robust performance

PrimaVision Compact for CDM

High-quality, compact and lightweight HID electronic gear for optimal and reliable performance of 20, 35, 50 and 70 W CDM lamps

Benefits

- Optimal lamp performance thanks to minimal lamp power tolerance
- CDM lamp life increased by up to 30%
- Eliminates all visible lamp flicker

Features

- Minimal lamp power spread
- Low gear energy losses
- Lamp end-of-life detection
- High Tambient and Tcase temperatures
- Long lifetime of 40,000 hours


Application

- Accent and decorative lighting for shops, public spaces, lobbies and offices
- Suitable for indoor use only

Versions



HID-PV C 35 & 70 /S



HID-PV C 35, 50 & 70 /P

PrimaVision Compact for CDM

Versions








HID-PV C 35 /I CDM 220-240V
50/60Hz NG



HID-PV C 50 /I CDM 220-240V
50/60Hz

Dimensional drawing



Product	D1	C1	A1	A2	B1
HID-PV C 50 /I CDM 220-240V 50/60Hz	4.8 mm	34.5 mm	188.0 mm	170.0 mm	82.7 mm
HID-PV C 70 /I CDM 220-240V 50/60Hz NG	4.8 mm	34.5 mm	188.0 mm	170.0 mm	82.7 mm
HID-PV C 35 /I CDM 220-240V 50/60Hz NG	4.8 mm	34.5 mm	188.0 mm	170.0 mm	82.7 mm

Product	D1	C1	A1	A2	B1
HID-PV C 50 /S CDM 220-240V 50/60Hz	4.9 mm	32.2 mm	109.6 mm	98.5 mm	74.4 mm
HID-PV C 70 /S CDM 220-240V 50/60Hz NG	4.9 mm	32.2 mm	109.6 mm	98.5 mm	74.4 mm
HID-PV C 35 /S CDM 220-240V 50/60Hz NG	4.9 mm	32.2 mm	109.6 mm	98.5 mm	74.4 mm

Product	D1	C1	A1	A2	B1	B2
HID-PV C 70 /P CDM 220-240V 50/60Hz	4.9 mm	29.6 mm	106.6 mm	98.5 mm	71.6 mm	63.7 mm
HID-PV C 35 /P CDM 220-240V 50/60Hz	4.9 mm	29.6 mm	106.6 mm	98.5 mm	71.6 mm	63.7 mm

PrimaVision Compact for CDM

Operating and Electrical

Input Frequency	50 to 60 Hz
Input Voltage	220 to 240 V

General Information

Number Of Lamps	1 piece/unit
Lamp Type	CDM

General Information

Order Code	Full Product Name	Number Of Products On MCB (16A Type B) (Nom)
913700652766	HID-PV C 35 /S CDM 220-240V 50/60Hz NG	24
913700652966	HID-PV C 70 /S CDM 220-240V 50/60Hz NG	20
913700652866	HID-PV C 35 /P CDM 220-240V 50/60Hz	24
913700653066	HID-PV C 70 /P CDM 220-240V 50/60Hz	20

Order Code	Full Product Name	Number Of Products On MCB (16A Type B) (Nom)
913700653166	HID-PV C 35 /I CDM 220-240V 50/60Hz NG	24
913700653266	HID-PV C 70 /I CDM 220-240V 50/60Hz NG	20
913700664966	HID-PV C 50 /S CDM 220-240V 50/60Hz	24
913700665166	HID-PV C 50 /I CDM 220-240V 50/60Hz	24

Mechanical and Housing

Order Code	Full Product Name	Housing
913700652766	HID-PV C 35 /S CDM 220-240V 50/60Hz NG	/S
913700652966	HID-PV C 70 /S CDM 220-240V 50/60Hz NG	/S
913700652866	HID-PV C 35 /P CDM 220-240V 50/60Hz	/P
913700653066	HID-PV C 70 /P CDM 220-240V 50/60Hz	/P

Order Code	Full Product Name	Housing
913700653166	HID-PV C 35 /I CDM 220-240V 50/60Hz NG	/I
913700653266	HID-PV C 70 /I CDM 220-240V 50/60Hz NG	/I
913700664966	HID-PV C 50 /S CDM 220-240V 50/60Hz	/S
913700665166	HID-PV C 50 /I CDM 220-240V 50/60Hz	/I

System characteristics

Order Code	Full Product Name	Rated Ballast-Lamp Power
913700652766	HID-PV C 35 /S CDM 220-240V 50/60Hz NG	35 W
913700652966	HID-PV C 70 /S CDM 220-240V 50/60Hz NG	70 W
913700652866	HID-PV C 35 /P CDM 220-240V 50/60Hz	35 W
913700653066	HID-PV C 70 /P CDM 220-240V 50/60Hz	70 W

Order Code	Full Product Name	Rated Ballast-Lamp Power
913700653166	HID-PV C 35 /I CDM 220-240V 50/60Hz NG	35 W
913700653266	HID-PV C 70 /I CDM 220-240V 50/60Hz NG	70 W
913700664966	HID-PV C 50 /S CDM 220-240V 50/60Hz	50 W
913700665166	HID-PV C 50 /I CDM 220-240V 50/60Hz	50 W

