

Motion detector

IS 2160 ECO

EAN 4007841606015



Functional description

Inexpensive, good and ideally suited to small-type premises, garage approaches and entrance ways. Not only impressive with outstanding value for money, this sensor also provides incredible flexibility: the detection zone can be adjusted to suit any situation simply by tilting and turning the sensor head.

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	113 x 78 x 73 mm
Mains power supply	230 – 240 V , 50 / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Type of installation	Surface wiring
Switching zones	260 Schaltzonen
Electronic scalability	No
Mechanical scalability	No
Optimum mounting height	2 m
Detection angle	160 °
Angle of aperture	40 °
Sneak-by guard	No
Capability of masking out individual segments	Yes
Reach, radial	r = 3 m (13 m²)
Reach, tangential	r = 12 m (201 m²)
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 min
Switching output 1, resistive	600 W
Switching output 1, number of LEDs / fluorescent lamps	4 stk.
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	white

Motion detector

IS 2160 ECO

EAN 4007841606015

Sensorenerfassungsbereich 1

