

Motion detector

IS D 360

EAN 4007841601317



Functional description

Control spotlights in suspended ceilings the more or less invisible way. The IS D360 fits in any standard spotlight surround. This is why at first glance it also looks like a normal lamp (e.g. GU10). The multi-lens only becomes apparent after taking a closer look. Cleverly integrated sensor technology from STEINEL.

Technical specifications

Type	Motion detectors
Dimensions (Ø x H)	82 x 83 mm
Mains power supply	230 – 240 V , 50 / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors
Type of installation	Concealed wiring
Switching zones	720 Schaltzonen
Electronic scalability	No
Mechanical scalability	No
Optimum mounting height	2,5 m
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, tangential	Ø 16 m (201 m²)
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	5 s – 20 min
Switching output 1, resistive	1000 W
Constant-lighting control	No
Basic light level function	No
With remote control	No
Interconnection	Yes
IP rating	IP20
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years

Motion detector

IS D 360

EAN 4007841601317

Sensorenerfassungsbereich 1

