
Photo-cell-controlled light

LN 710 LED

Anthracite EAN 4007841 053161



























3000K warm-white

Twilight switch

soft light start

energy sav

manufacture's warranty steinel.de/garantie

ntie

TüV Nord G

n

manufacture's warranty steinel.de/garantie

Function description

Beautiful light in pure form. Quite simply, the attractive outdoor light without motion detector always cuts a fine figure whether ON or OFF. The LN 710 LED is made of UV-resistant plastic and features a modern aluminium designer-style element. The warm-white light (3000 K) sets off building walls with absolute competence. With photo-cell controller, automatic lighting at night and optional night-economy mode. Available in anthracite and silver.

Technical specifications

Dimensions (L x W x H)	260 x 140 x 63 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	Light sensor
Output	8,6 W
Interconnection	No
Luminous flux	670 lm
Colour temperature	3000 K
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	No

Mechanical scalability	No
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Basic light level function	No
Soft light start	Yes
Impact resistance	IK03
IP rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
With remote control	No
Cover material	sticker
Version	Anthracite
PU1, EAN	4007841053161

Photo-cell-controlled light

LN 710 LED

Anthracite EAN 4007841 053161



Dimension Drawing

