




Presto LED



A functional LED lighting system made of steel sheet. Possibility to choose one of two lighting beams DI or DI-IN. Thanks to the linear joints (not in the set) the luminaire can be easily connected in line.

Materials: powder painted steel sheet body (standard colour: white), satin parabolic louver PAR-S, internal OPAL diffuser protecting LEDs

Installation: suspended, surface mounted (only DI versions)

Accessories: simple and electric suspensions, invisible linear joints, end caps

Power: 230 V

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Type of equipment	AC
Voltage rating	220 ... 240 V
Light source included	Yes

MECHANICAL DATA

Type of installation	Universal
Housing material	Steel sheet
Designed for light-line	Yes
Electrical track connection	No

INFORMATION

Colour	White
Operating temperature range	-15 ... 40 °C
Rotated model	No

CERTIFICATES

Degree of protection (IP)	IP20
Degree of protection (IP) / top/	IP20
Class of protection	I
CE	Yes

LIGHT DATA

Light colour	White
Color rendering index	80
Light distribution	Wide beam
Class of luminaire	I
Light output degradation	B10
Lumen maintenance	L90
Lifetime	> 54000 h
MacAdam	SDCM 3
Lamp Lumen Maintenance Factor (after 60 000h)	89 %

OPTICAL DATA

Louver/ shutter	PAR-S
Diffuser colour	White
Diffuser material	None
Reflector	Mat

AVAILABLE VARIANTS

Product code	Luminaire power [W]	Light source power [W]	Type of LED	Light source luminous flux [lm]	Luminaire luminous flux [lm]	Light source luminous efficacy [lm/W]	Luminaire's luminous efficacy [lm/W]	Luminaire's luminous efficiency [%]	Direct-/indirect independently controlled		Colour temperature
PX0759401	31	1x28	5622	4580	3550	164	115	78	No	DI	3000K
PX0759408	31	1x28	5623	4720	3660	169	118	78	No	DI	4000K
PX0759415	38	1x35	5626	5720	4430	163	117	77	No	DI	3000K
PX0759422	38	1x35	5627	5900	4570	169	120	77	No	DI	4000K

AVAILABLE VARIANTS

Product code	Luminaire power [W]	Light source power [W]	Type of LED	Light source luminous flux [lm]	Luminaire luminous flux [lm]	Light source luminous efficacy [lm/W]	Luminaire's luminous efficacy [lm/W]	Luminaire's luminous efficiency [%]	Direct-/indirect independently controlled		Colour temperature
PX0759429	46	1×42	5624	7240	5840	172	127	81	yes	DI/IN	3000K
PX0759436	46	1×42	5625	7460	6020	178	131	81	yes	DI/IN	4000K
PX0759443	60	1×55	5628	9060	7310	165	122	81	yes	DI/IN	3000K
PX0759450	60	1×55	5629	9340	7540	170	126	81	yes	DI/IN	4000K

DIMENSIONS



Product code	L [mm]	W [mm]	H [mm]
PX0759401	1145	125	52
PX0759408	1145	125	52
PX0759415	1435	125	52
PX0759422	1435	125	52
PX0759429	1145	125	58
PX0759436	1145	125	58
PX0759443	1435	125	58
PX0759450	1435	125	58

L = Length | W = Width | H = Height / Depth

ACCESSORIES

Structural element

Presto LED End cap
Pieces in set: 1

PX0759485

White

Connecting element

Presto LED Linear joint
Pieces in set: 2

PX0759492

Grey