


Sensor-switched indoor light

# RS PRO LED P2

warm white

EAN 4007841 056100

**STEINEL**<sup>®</sup>  
PROFESSIONAL



## Function description

Circular classic. Perfect shape. Perfect efficiency. The perfect switched indoor light . The RS PRO LED P2 integrates harmoniously into corridors, hallways and stairwells. It combines timeless design and extremely easy installation with pioneering technology and unbeatable efficiency. As many as ten lights can be interconnected by cable. Output: 16 W with 1730 lm, 3000 K.

## Technical specifications

Dimensions (Ø x H)	320 x 110 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	High frequency
Output	16 W
Interconnection	Yes
Luminous flux	1730 lm
Colour temperature	3000 K
Colour Rendering Index CRI	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L80B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	Yes
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °

Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 8 m (50 m²)
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 Min.
Basic light level function	Yes
Basic light level function time	10/30 min, all night
Soft light start	Yes
Impact resistance	IK03
IP rating	IP54
Protection class	II
Ambient temperature	-10 – 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	5 years
Version	warm white
PU1, EAN	4007841056100

Sensor-switched indoor light


# RS PRO LED P2

warm white

EAN 4007841 056100

**STEINEL**<sup>®</sup>  
PROFESSIONAL


## Detection Zone




Mögliche Montagehöhe: 2,00 m – 4,00 m

Orange: radial und tangential

## Dimension Drawing




## Light Distribution Curve



Output	16 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Luminous flux	1730 lm
Colour temperature	3000 K
Colour Rendering Index CRI	80-89
LED life expectancy (max. °C)	50000 h
LED cooling system	Passive Thermo Control

## Slave/wireless master interconnection circuit diagram



Sensor-switched indoor light

# RS PRO LED P2

warm white

EAN 4007841 056100



## Master/master interconnection circuit diagram

