



VIP Mini LED



VIP Mini, a new, subtle and miniaturized lighting luminaire, is enlarging the offer of VIP products. The body made of aluminum profile, the direct (DI) and indirect (IN) lighting beam. Light source: LEDs. As in the case of VIP, the additional accessories allow various configurations of lighting luminaires.

Materials: Powder painted aluminum profile (standard color: grey); microprismatic diffuser (MPRM).

Installation: Surface mounted, wall mounted, suspended

Accessories: Joints (linear, 90°, T, X, wall, ceiling); suspensions (simple, electric), end caps.

Power: 230V, DALI, 1-10 regulations on request. Not available with emergency module.

ELECTRICAL DATA

Light source	LED
Number of light sources	1
Type of equipment	AC
Voltage rating	220 ... 240 V
Light source included	Yes
Type of LED	5630

MECHANICAL DATA

Housing material	Aluminum
------------------	----------

INFORMATION

Colour	Grey
Operating temperature range	-15 ... 40 °C

CERTIFICATES

Degree of protection (IP)	IP20
Degree of protection (IP) / top/	IP20
Class of protection	I
Light source protection	Yes
Energy class	A+
CE	Yes
PZH	Yes
EAC	Yes

LIGHT DATA

Light colour	White
Color rendering index	80
Light distribution	Mid beam
Class of luminaire	I
Light output degradation	B10
Lumen maintenance	L90
Lifetime	> 54000 h
MacAdam	SDCM 3
Lamp Lumen Maintenance Factor (after 60 000h)	89 %

OPTICAL DATA

Louver/ shutter	MPRM
Diffuser colour	Transparent
Diffuser material	Prismatic plastic



AVAILABLE VARIANTS

Product code	Luminaire power [W]	Type of installation	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Colour temperature [K]		Other	Info	Weight [kg]
PX0921061	31	Universal	3388	109	3000	DI	bez klapek	DI	1.90

AVAILABLE VARIANTS

Product code	Luminaire power [W]	Type of installation	Luminaire luminous flux [lm]	Luminaire's luminous efficacy [lm/W]	Colour temperature [K]		Other	Info	Weight [kg]
PX0921068	31	Universal	3454	111	4000	DI	bez klapek	DI	1.90
PX0921075	38	Universal	4290	113	3000	DI	bez klapek	DI	2.40
PX0921082	38	Universal	4378	115	4000	DI	bez klapek	DI	2.40
PX0921001	31	Universal	3388	109	3000	DI	-	DI	2.00
PX0921008	31	Universal	3454	111	4000	DI	-	DI	2.00
PX0921015	38	Universal	4290	113	3000	DI	-	DI	2.50
PX0921022	38	Universal	4378	115	4000	DI	-	DI	2.50
PX0921029	31	Suspended	3388	109	3000	IN	-	IN	2.00
PX0921036	31	Suspended	3454	111	4000	IN	-	IN	2.00
PX0921043	38	Suspended	4290	113	3000	IN	-	IN	2.50
PX0921050	38	Suspended	4378	115	4000	IN	-	IN	2.50

DIMENSIONS



Product code	L [mm]	W [mm]	H [mm]
PX0921061	1165	46	46
PX0921068	1165	46	46
PX0921075	1455	46	46
PX0921082	1455	46	46
PX0921001	1320	46	46
PX0921008	1320	46	46
PX0921015	1620	46	46
PX0921022	1620	46	46
PX0921029	1320	46	46
PX0921036	1320	46	46
PX0921043	1620	46	46
PX0921050	1620	46	46

L = Length | W = Width | H = Height / Depth

MOUNTING HOLES

Product code	A [mm]
PX0921061	965
PX0921068	965
PX0921075	1255
PX0921082	1255
PX0921001	1210
PX0921008	1210
PX0921015	1510
PX0921022	1510
PX0921029	1245
PX0921036	1245
PX0921043	1545
PX0921050	1545

A = Spacing length

ACCESSORIES

Electric element



Electrical suspension
Pieces in set: 1

PX0922021

Grey

PX0922032

White

Structural element



VIP Mini End Cap

PX0922425

Grey

Connecting element



VIP Mini Invisible linear joint Set (2 pcs)
Pieces in set: 2

PX0922405

Grey



VIP Mini 90° joint

PX0922410

Grey



VIP Mini T joint

PX0922415

1x

Grey



VIP Mini Cross joint

PX0922420

1x

Grey

Installation element



VIP Mini Ceiling joint Set (2 pcs)
Pieces in set: 2

PX0922435

Grey



VIP Mini Wall joint (2 pcs)
Pieces in set: 2

PX0922430

Grey



Simple suspension

PX0922143