



# CoreLine Waterproof – the clear choice for LED

## CoreLine Waterproof

Whether for a new building or renovation of an existing space, customers want lighting solutions that provide quality of light and substantial energy and maintenance savings. The new CoreLine Waterproof range of LED products can be used to replace traditional waterproof luminaires with fluorescent lamps. The process of selecting, installing and maintaining is so easy – it's a simple switch. InterAct Ready luminaires with integrated wireless communications in this family available, to be used with InterAct gateways, sensors and software.

### Benefits

- Up to 64% energy savings compared with TL-D
- Reliable LED technology, ensuring maintenance-free installation and a long lifetime
- Direct replacement for conventional waterproof luminaires in terms of light performance, installation flexibility and length

### Features

- Can be used to replace traditional waterproof luminaires ranging from 18 to 58 W TL-D
- Wide-beam light distribution
- Diffuser with optical element ensures visual comfort
- Ceiling-mounted bracket and suspension hooks included; installation can be made vandal-proof by additional screw fixation of mounting brackets
- Vandal-proof by additional screw fixation of mounting brackets
- Optional waterproof external connector for easier installation (WEC)
- Optional emergency lighting

### Application

- Parking garages
- Warehouses
- General lighting

### Specifications

# CoreLine Waterproof

Type	WT120C
Light source	LED module
Power	17.6 W (LED18S L600 version) 23.5 W (LED22S L1200 version) 32 W (LED40S L1200 version) 29.5 W (LED34S L1500 version) 48 W (LED60S L1500 version)
Beam angle	60°
Luminous flux	2100 lm (LED18S L600 version) 2900 lm (LED22S L1200 version) 4100 lm (LED40S L1200 version) 3500 lm (LED34S L1500 version) 6000 lm (LED60S L1500 version)
Correlated Color Temperature	4000 K
Color Rendering Index	≥ 80
Lumen maintenance at median useful life* 50000 h	L75
Control gear failure rate at median useful life 50000 h	5%
Performance Ambient Temperature Tq	+25 °C

Operating temperature range	-20 to +35 °C
Driver	Built-in, replaceable
Mains voltage	220-240V / 50-60 Hz
Dimming	DALI Wireless Dim
Material	Housing: injection molded polycarbonate Diffuser: injection molded polycarbonate Closing clips: stainless spring steel
Color	Grey (RAL 7035)
Optical cover	Polycarbonate, clear with texture applied at the inside
Connection	Internal push-in connection with cable gland Optional: Waterproof External Connector (WEC) for easier installation
Maintenance	No internal cleaning required
Installation	Fixation with ceiling mounted bracket (vandal-proof by additional screw fixation) Through-wiring possible Suspension possible After electrical installation in housing luminaire is closed by optical cover and closing clips
Options	Emergency lighting 3 hours duration
Remarks	All mounting accessories are included

## Versions



CoreLine Waterproof WT120C luminaire



Coreline Waterproof

## Product details




Stainless spring steel clips for fast closing of the luminaire



Electrical connection between LED driver and diffuser with integrated LED source

Product details



Ceiling bracket and anti-vandal screws



Extra cable gland and stopper



Easy installation



Easy installation



Easy installation



Ceiling bracket and anti-vandal screws



Ceiling bracket with suspension and anti-vandal screws



LED module integrated in the cover

Product details

Side view



Front view




Close up anti-vandal screw



CoreLine\_Waterproof\_DOB-DP01.tif



CoreLine\_Waterproof\_DOB-DP02.tif



## Application Conditions

Suitable for random switching	Yes (relates to presence/movement detection and daylight harvesting)
-------------------------------	--

## Approval and Application

Mech. impact protection code	IK08
Ingress protection code	IP65

## General Information

CE mark	CE mark
Protection class IEC	Safety class I
Driver included	Yes
ENEC mark	ENEC mark
Flammability mark	For mounting on normally flammable surfaces
Glow-wire test	Temperature 850 °C, duration 30 s
Lamp family code	-
Light source replaceable	No
Number of gear units	1 unit
Optic type	-
Product Family Code	WT120C

## Initial Performance (IEC Compliant)

Initial chromaticity	(0.38, 0.38) SDCM <3
Init. Corr. Color Temperature	4000 K
Init. Color Rendering Index	≥80
Luminous flux tolerance	+/-10%

## Mechanical and Housing

Color	Gray
-------	------

## Application Conditions

Order Code	Full Product Name	Ambient temperature range	Maximum dim level
910500453335	WT120C LED18S/840 PSU L600	-20 to +35 °C	Not applicable
910500453336	WT120C LED22S/840 PSU L1200	-20 to +35 °C	Not applicable
910500453337	WT120C LED34S/840 PSU L1500	-20 to +35 °C	Not applicable
910500453338	WT120C LED40S/840 PSU L1200	-20 to +35 °C	Not applicable
910500453339	WT120C LED60S/840 PSU L1500	-20 to +35 °C	Not applicable
910500454298	WT120C LED22S/840 PSU L1200 EL1	0 to +25 °C	Not applicable
910500454299	WT120C LED40S/840 PSU L1200 EL1	0 to +25 °C	Not applicable
910500454301	WT120C LED34S/840 PSU L1500 EL1	0 to +25 °C	Not applicable
910500454302	WT120C LED60S/840 PSU L1500 EL1	0 to +25 °C	Not applicable
910500454303	WT120C LED22S/840 PSU L1200 EL3	0 to +25 °C	Not applicable
910500454304	WT120C LED40S/840 PSU L1200 EL3	0 to +25 °C	Not applicable
910500454305	WT120C LED34S/840 PSU L1500 EL3	0 to +25 °C	Not applicable
910500454306	WT120C LED60S/840 PSU L1500 EL3	0 to +25 °C	Not applicable
910500458243	WT120C LED18S/840 PSD L600	-25 to +35 °C	1%
910500458244	WT120C LED22S/840 PSD L1200	-25 to +35 °C	1%
910500458245	WT120C LED34S/840 PSD L1500	-25 to +35 °C	1%
910500458246	WT120C LED40S/840 PSD L1200	-25 to +35 °C	1%
910500458247	WT120C LED60S/840 PSD L1500	-25 to +35 °C	1%
910500458248	WT120C LED22S/840 PSD L1200 EL3	0 to +25 °C	1%
910500458249	WT120C LED40S/840 PSD L1200 EL3	0 to +25 °C	1%
910500458250	WT120C LED34S/840 PSD L1500 EL3	0 to +25 °C	1%
910500458251	WT120C LED60S/840 PSD L1500 EL3	0 to +25 °C	1%
910500458794	WT120C LED22S/840 PSU TW3 L1200	-20 to +35 °C	Not applicable
910500458795	WT120C LED34S/840 PSU TW3 L1500	-20 to +35 °C	Not applicable
910500458796	WT120C LED40S/840 PSU TW3 L1200	-20 to +35 °C	Not applicable
910500458797	WT120C LED60S/840 PSU TW3 L1500	-20 to +35 °C	Not applicable
910500465266	WT120C LED40S/840 IA1 L1200	-20 to +35 °C	-
910500465267	WT120C LED60S/840 IA1 L1500	-20 to +35 °C	-
910500465326	WT120C LED40S/840 IA1 L1200 EL3	0 to +25 °C	1%
910500465327	WT120C LED60S/840 IA1 L1500 EL3	0 to +25 °C	1%
910500465651	WT120C LED80S/840 PSU L1500	-25 to +35 °C	Not applicable
910500465652	WT120C LED80S/840 PSD L1500	-25 to +35 °C	1%
910500465653	WT120C LED80S/840 PSU TW3 L1500	-25 to +35 °C	Not applicable
910500465654	WT120C LED80S/840 PSU L1500 EL3	0 to +25 °C	Not applicable
910500459299	WT120C LED40S/840 PSU WEC L1200	-20 to +35 °C	Not applicable
910500459301	WT120C LED40S/840 PSU TW1 WEC L1200	-20 to +35 °C	Not applicable
910500459302	WT120C LED60S/840 PSU WEC L1500	-20 to +35 °C	Not applicable
910500459303	WT120C LED60S/840 PSU TW1 WEC L1500	-20 to +35 °C	Not applicable

## Controls and Dimming

Order Code	Full Product Name	Dimmable	Order Code	Full Product Name	Dimmable
910500453335	WT120C LED18S/840 PSU L600	No	910500454302	WT120C LED60S/840 PSU L1500 EL1	No
910500453336	WT120C LED22S/840 PSU L1200	No	910500454303	WT120C LED22S/840 PSU L1200 EL3	No
910500453337	WT120C LED34S/840 PSU L1500	No	910500454304	WT120C LED40S/840 PSU L1200 EL3	No
910500453338	WT120C LED40S/840 PSU L1200	No	910500454305	WT120C LED34S/840 PSU L1500 EL3	No
910500453339	WT120C LED60S/840 PSU L1500	No	910500454306	WT120C LED60S/840 PSU L1500 EL3	No
910500454298	WT120C LED22S/840 PSU L1200 EL1	No	910500458243	WT120C LED18S/840 PSD L600	Yes
910500454299	WT120C LED40S/840 PSU L1200 EL1	No	910500458244	WT120C LED22S/840 PSD L1200	Yes
910500454301	WT120C LED34S/840 PSU L1500 EL1	No	910500458245	WT120C LED34S/840 PSD L1500	Yes

## CoreLine Waterproof

Order Code	Full Product Name	Dimmable
910500458246	WT120C LED40S/840 PSD L1200	Yes
910500458247	WT120C LED60S/840 PSD L1500	Yes
910500458248	WT120C LED22S/840 PSD L1200 EL3	Yes
910500458249	WT120C LED40S/840 PSD L1200 EL3	Yes
910500458250	WT120C LED34S/840 PSD L1500 EL3	Yes
910500458251	WT120C LED60S/840 PSD L1500 EL3	Yes
910500458794	WT120C LED22S/840 PSU TW3 L1200	No
910500458795	WT120C LED34S/840 PSU TW3 L1500	No
910500458796	WT120C LED40S/840 PSU TW3 L1200	No
910500458797	WT120C LED60S/840 PSU TW3 L1500	No
910500465266	WT120C LED40S/840 IA1 L1200	Wireless Dim

Order Code	Full Product Name	Dimmable
910500465267	WT120C LED60S/840 IA1 L1500	Wireless Dim
910500465326	WT120C LED40S/840 IA1 L1200 EL3	Yes
910500465327	WT120C LED60S/840 IA1 L1500 EL3	Yes
910500465651	WT120C LED80S/840 PSU L1500	No
910500465652	WT120C LED80S/840 PSD L1500	Yes
910500465653	WT120C LED80S/840 PSU TW3 L1500	No
910500465654	WT120C LED80S/840 PSU L1500 EL3	No
910500459299	WT120C LED40S/840 PSU WEC L1200	No
910500459301	WT120C LED40S/840 PSU TW1 WEC L1200	No
910500459302	WT120C LED60S/840 PSU WEC L1500	No
910500459303	WT120C LED60S/840 PSU TW1 WEC L1500	No

### Operating and Electrical

Order Code	Full Product Name	Input Voltage
910500453335	WT120C LED18S/840 PSU L600	220 to 240 V
910500453336	WT120C LED22S/840 PSU L1200	220 to 240 V
910500453337	WT120C LED34S/840 PSU L1500	220 to 240 V
910500453338	WT120C LED40S/840 PSU L1200	220 to 240 V
910500453339	WT120C LED60S/840 PSU L1500	220 to 240 V
910500454298	WT120C LED22S/840 PSU L1200 EL1	220 to 240 V
910500454299	WT120C LED40S/840 PSU L1200 EL1	220 to 240 V
910500454301	WT120C LED34S/840 PSU L1500 EL1	220 to 240 V
910500454302	WT120C LED60S/840 PSU L1500 EL1	220 to 240 V
910500454303	WT120C LED22S/840 PSU L1200 EL3	220 to 240 V
910500454304	WT120C LED40S/840 PSU L1200 EL3	220 to 240 V
910500454305	WT120C LED34S/840 PSU L1500 EL3	220 to 240 V
910500454306	WT120C LED60S/840 PSU L1500 EL3	220 to 240 V
910500458243	WT120C LED18S/840 PSD L600	220 to 240 V
910500458244	WT120C LED22S/840 PSD L1200	220 to 240 V
910500458245	WT120C LED34S/840 PSD L1500	220 to 240 V
910500458246	WT120C LED40S/840 PSD L1200	220 to 240 V
910500458247	WT120C LED60S/840 PSD L1500	220 to 240 V
910500458248	WT120C LED22S/840 PSD L1200 EL3	220 to 240 V

Order Code	Full Product Name	Input Voltage
910500458249	WT120C LED40S/840 PSD L1200 EL3	220 to 240 V
910500458250	WT120C LED34S/840 PSD L1500 EL3	220 to 240 V
910500458251	WT120C LED60S/840 PSD L1500 EL3	220 to 240 V
910500458794	WT120C LED22S/840 PSU TW3 L1200	220-240 V
910500458795	WT120C LED34S/840 PSU TW3 L1500	220-240 V
910500458796	WT120C LED40S/840 PSU TW3 L1200	220-240 V
910500458797	WT120C LED60S/840 PSU TW3 L1500	220-240 V
910500465266	WT120C LED40S/840 IA1 L1200	220 to 240 V
910500465267	WT120C LED60S/840 IA1 L1500	220 to 240 V
910500465326	WT120C LED40S/840 IA1 L1200 EL3	220 to 240 V
910500465327	WT120C LED60S/840 IA1 L1500 EL3	220 to 240 V
910500465651	WT120C LED80S/840 PSU L1500	220 to 240 V
910500465652	WT120C LED80S/840 PSD L1500	220 to 240 V
910500465653	WT120C LED80S/840 PSU TW3 L1500	220 to 240 V
910500465654	WT120C LED80S/840 PSU L1500 EL3	220 to 240 V
910500459299	WT120C LED40S/840 PSU WEC L1200	220 to 240 V
910500459301	WT120C LED40S/840 PSU TW1 WEC L1200	220 to 240 V
910500459302	WT120C LED60S/840 PSU WEC L1500	220 to 240 V
910500459303	WT120C LED60S/840 PSU TW1 WEC L1500	220 to 240 V

### General Information (1/2)

Order Code	Full Product Name	Beam angle of light source	Cap-Base	Optical cover/lens type	Emergency lighting
910500453335	WT120C LED18S/840 PSU L600	-	-	Polycarbonate bowl/cover	-
910500453336	WT120C LED22S/840 PSU L1200	-	-	Polycarbonate bowl/cover	-
910500453337	WT120C LED34S/840 PSU L1500	-	-	Polycarbonate bowl/cover	-

Order Code	Full Product Name	Beam angle of light source	Cap-Base	Optical cover/lens type	Emergency lighting
910500453338	WT120C LED40S/840 PSU L1200	120 °	-	Polycarbonate bowl/cover	-
910500453339	WT120C LED60S/840 PSU L1500	120 °	-	Polycarbonate bowl/cover	-
910500454298	WT120C LED22S/840 PSU L1200 EL1	-	-	Polycarbonate bowl/cover	Emergency lighting 1 hour duration

Order Code	Full Product Name	Beam angle of light source	Cap-Base	Optical cover/lens type	Emergency lighting
910500454299	WT120C LED40S/840 PSU L1200 EL1	-	-	Polycarbonate bowl/cover	Emergency lighting 1 hour duration
910500454301	WT120C LED34S/840 PSU L1500 EL1	-	-	Polycarbonate bowl/cover	Emergency lighting 1 hour duration
910500454302	WT120C LED60S/840 PSU L1500 EL1	-	-	Polycarbonate bowl/cover	Emergency lighting 1 hour duration
910500454303	WT120C LED22S/840 PSU L1200 EL3	-	-	Polycarbonate bowl/cover	Emergency lighting 3 hours duration
910500454304	WT120C LED40S/840 PSU L1200 EL3	-	-	Polycarbonate bowl/cover	Emergency lighting 3 hours duration
910500454305	WT120C LED34S/840 PSU L1500 EL3	-	-	Polycarbonate bowl/cover	Emergency lighting 3 hours duration
910500454306	WT120C LED60S/840 PSU L1500 EL3	-	-	Polycarbonate bowl/cover	Emergency lighting 3 hours duration
910500458243	WT120C LED18S/840 PSD L600	-	-	Polycarbonate bowl/cover	-
910500458244	WT120C LED22S/840 PSD L1200	-	-	Polycarbonate bowl/cover	-
910500458245	WT120C LED34S/840 PSD L1500	-	-	Polycarbonate bowl/cover	-
910500458246	WT120C LED40S/840 PSD L1200	-	-	Polycarbonate bowl/cover	-
910500458247	WT120C LED60S/840 PSD L1500	-	-	Polycarbonate bowl/cover	-
910500458248	WT120C LED22S/840 PSD L1200 EL3	-	-	Polycarbonate bowl/cover	Emergency lighting 3 hours duration
910500458249	WT120C LED40S/840 PSD L1200 EL3	-	-	Polycarbonate bowl/cover	Emergency lighting 3 hours duration
910500458250	WT120C LED34S/840 PSD L1500 EL3	-	-	Polycarbonate bowl/cover	Emergency lighting 3 hours duration
910500458251	WT120C LED60S/840 PSD L1500 EL3	-	-	Polycarbonate bowl/cover	Emergency lighting 3 hours duration

Order Code	Full Product Name	Beam angle of light source	Cap-Base	Optical cover/lens type	Emergency lighting
910500458794	WT120C LED22S/840 PSU TW3 L1200	120 °	-	-	-
910500458795	WT120C LED34S/840 PSU TW3 L1500	120 °	-	-	-
910500458796	WT120C LED40S/840 PSU TW3 L1200	120 °	-	-	-
910500458797	WT120C LED60S/840 PSU TW3 L1500	120 °	-	-	-
910500465266	WT120C LED40S/840 IA1 L1200	120 °	-	-	-
910500465267	WT120C LED60S/840 IA1 L1500	120 °	-	-	-
910500465326	WT120C LED40S/840 IA1 L1200 EL3	-	-	-	-
910500465327	WT120C LED60S/840 IA1 L1500 EL3	-	-	-	-
910500465651	WT120C LED80S/840 PSU L1500	120 °	-	-	-
910500465652	WT120C LED80S/840 PSD L1500	120 °	-	-	-
910500465653	WT120C LED80S/840 PSU TW3 L1500	120 °	-	-	-
910500465654	WT120C LED80S/840 PSU L1500 EL3	120 °	-	-	Emergency lighting 3 hours duration
910500459299	WT120C LED40S/840 PSU WEC L1200	-	-	-	-
910500459301	WT120C LED40S/840 PSU TW1 WEC L1200	-	-	-	-
910500459302	WT120C LED60S/840 PSU WEC L1500	-	-	-	-
910500459303	WT120C LED60S/840 PSU TW1 WEC L1500	-	-	-	-

## General Information (2/2)

## CoreLine Waterproof

Order Code	Full Product Name	Number of light		
		Gear	sources	UL mark
910500453335	WT120C LED18S/840 PSU L600	-	1 pc	-
910500453336	WT120C LED22S/840 PSU L1200	-	1 pc	-
910500453337	WT120C LED34S/840 PSU L1500	-	1 pc	-
910500453338	WT120C LED40S/840 PSU L1200	-	1 pc	-
910500453339	WT120C LED60S/840 PSU L1500	-	1 pc	-
910500454298	WT120C LED22S/840 PSU L1200 EL1	-	1 pc	-
910500454299	WT120C LED40S/840 PSU L1200 EL1	-	1 pc	-
910500454301	WT120C LED34S/840 PSU L1500 EL1	-	1 pc	-
910500454302	WT120C LED60S/840 PSU L1500 EL1	-	1 pc	-
910500454303	WT120C LED22S/840 PSU L1200 EL3	-	1 pc	-
910500454304	WT120C LED40S/840 PSU L1200 EL3	-	1 pc	-
910500454305	WT120C LED34S/840 PSU L1500 EL3	-	1 pc	-
910500454306	WT120C LED60S/840 PSU L1500 EL3	-	1 pc	-
910500458243	WT120C LED18S/840 PSD L600	-	1 pc	-
910500458244	WT120C LED22S/840 PSD L1200	-	1 pc	-
910500458245	WT120C LED34S/840 PSD L1500	-	1 pc	-
910500458246	WT120C LED40S/840 PSD L1200	-	1 pc	-
910500458247	WT120C LED60S/840 PSD L1500	-	1 pc	-
910500458248	WT120C LED22S/840 PSD L1200 EL3	-	1 pc	-
910500458249	WT120C LED40S/840 PSD L1200 EL3	-	1 pc	-

Order Code	Full Product Name	Number of light		
		Gear	sources	UL mark
910500458250	WT120C LED34S/840 PSD L1500 EL3	-	1 pc	-
910500458251	WT120C LED60S/840 PSD L1500 EL3	-	1 pc	-
910500458794	WT120C LED22S/840 PSU TW3 L1200	-	1 pc	-
910500458795	WT120C LED34S/840 PSU TW3 L1500	-	1 pc	-
910500458796	WT120C LED40S/840 PSU TW3 L1200	-	1 pc	-
910500458797	WT120C LED60S/840 PSU TW3 L1500	-	1 pc	-
910500465266	WT120C LED40S/840 IA1 L1200	-	-	-
910500465267	WT120C LED60S/840 IA1 L1500	-	-	-
910500465326	WT120C LED40S/840 IA1 L1200 EL3	-	-	-
910500465327	WT120C LED60S/840 IA1 L1500 EL3	-	-	-
910500465651	WT120C LED80S/840 PSU L1500	-	-	-
910500465652	WT120C LED80S/840 PSD L1500	-	-	-
910500465653	WT120C LED80S/840 PSU TW3 L1500	-	-	-
910500465654	WT120C LED80S/840 PSU L1500 EL3	-	-	-
910500459299	WT120C LED40S/840 PSU WEC L1200	-	-	-
910500459301	WT120C LED40S/840 PSU TW1 WEC L1200	-	-	-
910500459302	WT120C LED60S/840 PSU WEC L1500	-	-	-
910500459303	WT120C LED60S/840 PSU TW1 WEC L1500	-	-	-

### Initial Performance (IEC Compliant)

Order Code	Full Product Name	Initial LED	Initial luminous	Initial input
		luminaire efficacy	flux	power
910500453335	WT120C LED18S/840 PSU L600	119 lm/W	2100 lm	17.6 W
910500453336	WT120C LED22S/840 PSU L1200	123 lm/W	2900 lm	23.5 W
910500453337	WT120C LED34S/840 PSU L1500	119 lm/W	3500 lm	29.5 W
910500453338	WT120C LED40S/840 PSU L1200	115 lm/W	4100 lm	35.5 W
910500453339	WT120C LED60S/840 PSU L1500	125 lm/W	6000 lm	48 W
910500454298	WT120C LED22S/840 PSU L1200 EL1	98 lm/W	2900 lm	22.5 W
910500454299	WT120C LED40S/840 PSU L1200 EL1	104 lm/W	4100 lm	39.5 W
910500454301	WT120C LED34S/840 PSU L1500 EL1	106 lm/W	3500 lm	33 W
910500454302	WT120C LED60S/840 PSU L1500 EL1	115 lm/W	6000 lm	52 W
910500454303	WT120C LED22S/840 PSU L1200 EL3	98 lm/W	2900 lm	22.5 W
910500454304	WT120C LED40S/840 PSU L1200 EL3	104 lm/W	4100 lm	39.5 W
910500454305	WT120C LED34S/840 PSU L1500 EL3	106 lm/W	3500 lm	33 W
910500454306	WT120C LED60S/840 PSU L1500 EL3	115 lm/W	6000 lm	52 W

Order Code	Full Product Name	Initial LED	Initial luminous	Initial input
		luminaire efficacy	flux	power
910500458243	WT120C LED18S/840 PSD L600	114 lm/W	2100 lm	18.5 W
910500458244	WT120C LED22S/840 PSD L1200	118 lm/W	2900 lm	24.5 W
910500458245	WT120C LED34S/840 PSD L1500	117 lm/W	3500 lm	30 W
910500458246	WT120C LED40S/840 PSD L1200	112 lm/W	4100 lm	36.5 W
910500458247	WT120C LED60S/840 PSD L1500	121 lm/W	6000 lm	49.5 W
910500458248	WT120C LED22S/840 PSD L1200 EL3	98 lm/W	2900 lm	22.5 W
910500458249	WT120C LED40S/840 PSD L1200 EL3	104 lm/W	4100 lm	39.5 W
910500458250	WT120C LED34S/840 PSD L1500 EL3	106 lm/W	3500 lm	33 W
910500458251	WT120C LED60S/840 PSD L1500 EL3	115 lm/W	6000 lm	52 W
910500458794	WT120C LED22S/840 PSU TW3 L1200	123 lm/W	2900 lm	23.5 W
910500458795	WT120C LED34S/840 PSU TW3 L1500	119 lm/W	3500 lm	29.5 W
910500458796	WT120C LED40S/840 PSU TW3 L1200	115 lm/W	4100 lm	35.5 W
910500458797	WT120C LED60S/840 PSU TW3 L1500	125 lm/W	6000 lm	48 W



## CoreLine Waterproof

Order Code	Full Product Name	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910500465266	WT120C LED40S/840 IA1 L1200	112 lm/W	4100 lm	36.5 W
910500465267	WT120C LED60S/840 IA1 L1500	121 lm/W	6000 lm	49.5 W
910500465326	WT120C LED40S/840 IA1 L1200 EL3	104 lm/W	4100 lm	39.5 W
910500465327	WT120C LED60S/840 IA1 L1500 EL3	115 lm/W	6000 lm	52 W
910500465651	WT120C LED80S/840 PSU L1500	118 lm/W	8000 lm	68 W
910500465652	WT120C LED80S/840 PSD L1500	118 lm/W	8000 lm	68 W

Order Code	Full Product Name	Initial LED luminaire efficacy	Initial luminous flux	Initial input power
910500465653	WT120C LED80S/840 PSU TW3 L1500	118 lm/W	8000 lm	68 W
910500465654	WT120C LED80S/840 PSU L1500 EL3	113 lm/W	8000 lm	71 W
910500459299	WT120C LED40S/840 PSU WEC L1200	125 lm/W	4000 lm	32 W
910500459301	WT120C LED40S/840 PSU TW1 WEC L1200	125 lm/W	4000 lm	32 W
910500459302	WT120C LED60S/840 PSU WEC L1500	125 lm/W	6000 lm	48 W
910500459303	WT120C LED60S/840 PSU TW1 WEC L1500	125 lm/W	6000 lm	48 W

### Mechanical and Housing

Order Code	Full Product Name	Diameter	Width
910500453335	WT120C LED18S/840 PSU L600	-	-
910500453336	WT120C LED22S/840 PSU L1200	-	-
910500453337	WT120C LED34S/840 PSU L1500	-	-
910500453338	WT120C LED40S/840 PSU L1200	-	-
910500453339	WT120C LED60S/840 PSU L1500	-	-
910500454298	WT120C LED22S/840 PSU L1200 EL1	-	-
910500454299	WT120C LED40S/840 PSU L1200 EL1	-	-
910500454301	WT120C LED34S/840 PSU L1500 EL1	-	-
910500454302	WT120C LED60S/840 PSU L1500 EL1	-	-
910500454303	WT120C LED22S/840 PSU L1200 EL3	-	-
910500454304	WT120C LED40S/840 PSU L1200 EL3	-	-
910500454305	WT120C LED34S/840 PSU L1500 EL3	-	-
910500454306	WT120C LED60S/840 PSU L1500 EL3	-	-
910500458243	WT120C LED18S/840 PSD L600	-	-
910500458244	WT120C LED22S/840 PSD L1200	-	-
910500458245	WT120C LED34S/840 PSD L1500	-	-
910500458246	WT120C LED40S/840 PSD L1200	-	-
910500458247	WT120C LED60S/840 PSD L1500	-	-
910500458248	WT120C LED22S/840 PSD L1200 EL3	-	-

Order Code	Full Product Name	Diameter	Width
910500458249	WT120C LED40S/840 PSD L1200 EL3	-	-
910500458250	WT120C LED34S/840 PSD L1500 EL3	-	-
910500458251	WT120C LED60S/840 PSD L1500 EL3	-	-
910500458794	WT120C LED22S/840 PSU TW3 L1200	-	- mm
910500458795	WT120C LED34S/840 PSU TW3 L1500	-	- mm
910500458796	WT120C LED40S/840 PSU TW3 L1200	-	- mm
910500458797	WT120C LED60S/840 PSU TW3 L1500	-	-
910500465266	WT120C LED40S/840 IA1 L1200	-	-
910500465267	WT120C LED60S/840 IA1 L1500	-	-
910500465326	WT120C LED40S/840 IA1 L1200 EL3	-	-
910500465327	WT120C LED60S/840 IA1 L1500 EL3	-	-
910500465651	WT120C LED80S/840 PSU L1500	-	-
910500465652	WT120C LED80S/840 PSD L1500	-	-
910500465653	WT120C LED80S/840 PSU TW3 L1500	-	-
910500465654	WT120C LED80S/840 PSU L1500 EL3	-	-
910500459299	WT120C LED40S/840 PSU WEC L1200	-	-
910500459301	WT120C LED40S/840 PSU TW1 WEC L1200	-	-
910500459302	WT120C LED60S/840 PSU WEC L1500	-	-
910500459303	WT120C LED60S/840 PSU TW1 WEC L1500	-	-

