

																
FISHTAPE	RATTLE SNAKE NYLON		TIGER SNAKE HELICOIDAL FISHTAPE			VIPER SNAKE STRIP STEEL			GREEN SNAKE STEEL WIRE	COBRA SNAKE GLASSFIBER						
page	4-6		8-10			12-14			16	18-40						
ø FISHTAPE (mm)	3	4	4,5	5,2	5,8	4	6	10	4	3	4,5	6	7,5	9	11	15
OPTIMUM LENGHT (m)	from 5 to 15	from 5 to 30	from 10 to 30	from 20 to 50	from 30 to 40	from 10 to 30	from 30 to 50	from 60 to 90	from 10 to 20	from 5 to 30	from 15 to 40	from 30 to 70	from 50 to 90	from 60 to 120	from 100 to 250	from 200 to 300
ø TUBE (mm)	16-20	16-25	16-32	20-32	30-50	20-32	40-100	60-160	20-32	16-32	30-50	30-80	50-100	60-120	80-160	180-400
TURNING RADIUS (mm)	100	100	100	100	100	400	600	890	400	160	310	400	500	620	770	1200
BREAKING LOAD MATERIAL (kg)	270	470	250	350	450	650	900	2400	590	400	1200	2000	3200	4300	6200	14000
PULLING RESISTANCE - STARTING/ENDING JUNCTION (kg)	80	110	135	150	160	180	360	810	135	110	170	290	330	460	580	690
DURABILITY	low	low	high	high	high	low	low	low	good	good	good	very good	very good	very good	very good	very good